

TECHNICAL PARAMETERS

Product Code	KT005103	KT010103	KT015103	KT020103	KT020203	KT030203	KT050203	KT075303	KT100403	KT150603	KT200803
Capacity (Tonnes)	0.5	1	1.5	2(1)	2(2)	3	5	7.5	10	15	20
Standard lift (Mtr)	3	3	3	3	3	3	3	3	3	3	3
Number of falls	1	1	1	1	2	2	2	3	4	6	8
Load chain dia (mm)	6	6	8	8	6	8	10	10	10	10	10
Test load (Tonnes)	0.75	1.5	2.25	3	3	4.5	7.5	11.25	15	22.5	30
Effort required at capacity (Newton)	221	304	343	457	314	343	381	392	392	392	392
Dimension	A	138	164	198	198	164	198	228	367	367	598
	B	114	124	142	142	124	142	167	167	167	200
	C	271	360	453	453	490	570	690	720	720	1000
	D	21.5	27	30	30	30	37	46	54	54	72
	E	51	55	67	67	86	102	112	160	260	302
	F	24	28	40	40	42	46	57	82	82	140
	G	33	38	45	45	45	51	65	85	85	100
Extra weight per mtr. of extra lift (Kg)	1.7	1.7	2.3	2.3	2.5	3.7	5.3	7.5	9.7	14.2	19.4
Bare block weight (Kg)	5.3	6.5	12.5	13	8	13.5	24	37	40.5	70	100
Net weight with chain (Kg)	8.5	12	17	18	16	24	39	60	70.5	112	151.5

Extra Lift & higher sizes are available on request. Due to continual development of products, manufacturer reserves the right to modify design, dimensional parameters and component and composition of material without prior notice

