



Heavy duty

► **TECHNICAL PARAMETERS :**

Capacity	Tonnes	3.2			5			10			
Item Codes	KEWRH	410306-DS	410309-DS	410312-DS	410506-DS	410509-DS	410512-DS	411006-DS	411009-DS	411012-DS	
Lifting Height	Mtr.	6	9	12	6	9	12	6	9	12	
No Of Falls	Mtr.	4/1	4/1	4/1	4/1	4/1	4/1	4/1	4/1	4/1	
Wire Rope Dia	mm	6	6	6	8	8	8	11	11	11	
Wire Rope Construction	8 x k19+IWRC; Galvanized; LHOL; 2160N / MM2; Non Rotating Rope										
Duty Class	CLASS IV										
Lifting Speed	m/min	5/0.8	5/0.8	5/0.8	5/0.8	5/0.8	5/0.8	5/0.8	5/0.8	5/0.8	
Lifting Power	Kw	3.2/0.45	3.2/0.45	3.2/0.45	6/0.9	6/0.9	6/0.9	9.5/1.5	9.5/1.5	9.5/1.5	
Travelling Speed	m/min	16	16	16	16	16	16	16	16	16	
Travelling Power	Kw	0.4	0.4	0.4	0.65	0.65	0.65	0.4*2	0.4*2	0.4*2	
Dimension	H	mm	243	243	243	255	255	255	315	315	315
	C	mm	556	556	556	596	596	596	750	750	750
	A	mm	932	1082	1282	940	1090	1290	940	1090	1290
	B	mm	1087-1587	1087-1587	1087-1587	1095-1395	1095-1395	1095-1395	1282-1582	1282-1583	1282-1584
Beam Min-Max Flange Width (S)	mm	200-350	200-350	200-350	200-350	200-350	200-350	190-450	190-450	190-450	
G.W./N.W.	Kg	375/315	390/330	430/350	445/383	500/428	560/465	830/725	935/780	995/880	

Extra Lift & higher sizes are available on request. Due to continual development of products, manufacturer reserves the right to modify design, dimensional parameters and component and composition of material without prior notice