



TECHNICAL PARAMETERS

Model	Capacity (T)	Level	Rope Reeving	Lift Speed (m/min)	Lift Motor (kw)	Travel Speed (m/min)	Travel Motor (kw)	Width (mm)		Wire rope Diameter (mm)	Wheel (mm)	A (mm)	Head Room (mm)	Height (m)
								I Beam	H Beam					
KURH210209	2	M4	2/1	8	3/0.8	20/5	0.37/0.1	100-180	100-420	8	100	157	1050	9
KURH210212	2	M4	2/1	8	3/0.8	20/5	0.37/0.1	100-180	100-420	8	100	157	1050	12
KURH210218	2	M4	2/1	8	3/0.8	20/5	0.37/0.1	100-180	100-420	8	100	157	1050	18
KURH410306	3.2	M4	4/1	4.5	3/0.8	20/5	0.37/0.1	100-180	100-420	8	100	157	1000	6
KURH410309	3.2	M4	4/1	4.5	3/0.8	20/5	0.37/0.1	100-180	100-420	8	100	157	1000	9
KURH410312	3.2	M4	4/1	4.5	3/0.8	20/5	0.37/0.1	100-180	100-420	8	100	157	1000	12
KURH410609	6.3	M4	4/1	4	4.5/1.1	20/5	0.75/0.18	110-180	110-420	11	100	157	1100	9
KURH410612	6.3	M4	4/1	4	4.5/1.1	20/5	0.75/0.18	110-180	110-420	11	100	157	1100	12

Note: Hoisting & Cross Travel Motors are currently equipped with single speed
Creep / Variable / Dual Speed is optional